



YouTube

MO405N

Scan and see more!



POWER SUPPLY:	400V
MOTOR POWER:	1,1 kW
MAX. TORQUE SPINDLE:	1200 Nm
TABLE ROTATION SPEED:	6 /12 obr./min.
AIR SUPPLY:	8 -12 Bar
PUMP LIMITER:	up to 3.5 Bar with regulation
BUILT-IN INFLATOR:	No
EXTERNAL FASTENING:	8" - 22"
INTERNAL FASTENING:	10" - 24"
BEAD BRAKER:	3000 kg
MAX. WHEEL DIAMETER:	1200 mm (47")
MAX. WHEEL WIDTH:	350 mm (15")
NOISE LEVEL:	<70 dB
WEIGHT:	290 kg
SIZE OF THE PACKAGE:	91x110x107 cm

Pneumatically tilting main column ♦ Pneumatically locked head position ♦ Double table speed activated by switch ♦ Gun with pressure gauge ♦ Huge stock of protective caps ♦ An additional AL2 or AL3 arm can be used ♦ Possibility to use an automatic head

ACCESSORIES AS STANDARD WITH TYRE CHANGER



mounting spoon overlay 2 pcs ♦ solid assembly spoon 1 pc
 ♦ brush 1 pc ♦ gun with pressure gauge ♦ bucket 1 pc
 ♦ **overlay of the assembly table jaws 8 pcs / 2 sets** ♦ dehydrator and oiler with pressure gauge 1 pc ♦ **mounting foot cap 40 pieces**
 ♦ **2 sets / 2 pcs bead breaker pad**


POLISH PROJECT



Additional jaws slides




Gun with pressure gauge



Pneumatically tilting column wider at the base




Profiled assembly table from 10" to 24"



High-quality components



Strong bead breaker with a force of 3 tons



Extendable cassette with pedals



Double speed rotary table, controlled in a switch

OPTIONAL EQUIPMENT

AUTOMATIC HEAD



HELPING ARM AL2



HELPING ARM AL3

