



ECK ATF MOOVETECH

TECHNICAL DATA:

SUPPORTED OILS: POWER SUPPLY: FILTERS: TANK FOR NEW OIL: TANK FOR USED OIL: SCALE ACCURACY: PUMP PERFORMANCE: WTRYSK OLEJU: BUILT-IN WIFI MODULE, PRINTER: VEHICLE DATABASE: DISPLAY:: HOSE LENGTH: WORKING TEMPERATURE: VALVES: WEIGHT LOCK:



MACHINE INTERNAL CLEANING FUNCTION

230V/50Hz 2 FILTRY CZYSZCZĄCE 20 LITERS 25 LITERS 5g new and used oil, 5g cleaning liquid 9 I/min SCALABLE (DOSING BY OIL SCALES) STANDARD YES, PASSENGER CARS 7" COLORFUL TOUCH 3 METERS 5 ÷ 55 °C AUTOMATIC YES

DEXTRON II, III, IV, GENERIC, DB OIL

<u>Coffrend</u>




STATUS LIGHT



DOUBLE SYSTEM OIL FILTERING



CLEANING ADDITIVE TANK



LARGE 7" TOUCH DISPLAY CLEAR MENU IN ENGLISH



POSSIBILITY OF WIFI CONNECTION



3 METER HOSE SERVICE



BUILT-IN PRINTER



ECK ATF MOOVETECH






REFILLABLE OIL LEVEL



Ciroma

Fully automatic gearbox service station! Built-in vehicle database with wiring diagrams. **Automatic detection of the direction of oil circulation in the gearbox system, no need to worry about the order in which the service hose are connected!**











CASE WITH CONNECTORS ON STANDARD EQUIPMENT





ACCESSORIES (OPTIONAL)



ADDITIONAL OPTIONAL CASE OVERFLOW CONNECTORS

